

# M A T E R I A L   S A F E T Y   D A T A   S H E E T

2002 - No Leak Power Steering Sealer  
Part #2002

Gold Eagle Company  
4400 S. Kildare Blvd.  
Chicago, IL 60632-4372  
(773) 376-4400

\*\*\*\*\* HMIS RATINGS \*\*\*\*\*  
Health: 0   Flammability: 1   Reactivity: 0   Pers. Prot. Index: B

\*\*\*\*\* NFPA RATINGS \*\*\*\*\*  
Health: 0   Fire: 1   Reactivity: 0   Specific Hazard: None

---

## SECTION I   PRODUCT IDENTITY

---

Product/Trade Name(s): 2002 - No Leak Power Steering Sealer  
Part Number: 2002  
MSDS Date: 07/16/03  
CAS #: N/A  
Category: N/A  
Distributor: N/A  
Chemical Name: N/A  
Formula: N/A  
Brief Description: Seal swelling additive designed to reduce engine leaks.

---

## SECTION II   HAZARDOUS INGREDIENTS & EXPOSURE LIMITS

---

CHEMICAL NAME	CAS #	%	LIMIT VALUES
ADDITIVE PACKAGE (CAS#: MIXTURE)		30.00	N/A
REFINED PETROLEUM OIL (CAS# 64742-65-0)		70.00	N/A

---

## SECTION III   PHYSICAL/CHEMICAL CHARACTERISTICS

---

Boiling Point: 665 F. (352 C.)  
Vapor Pressure (mm Hg.): N/A  
Vapor Density (AIR = 1): >1.0  
Solubility in Water: Negligible  
% Volatile / Volume: Negligible  
Appearance and Odor: Amber, oil type liquid  
pH: N/A  
Specific Gravity (H2O = 1): 0.880

### Miscellaneous Information

Product is a combustible liquid. Keep away from heat and flames. Store below 150 F., do not apply high heat or flame to container. Keep separate from strong oxidizing agents. Empty containers may contain product residue which could include flammable or explosive vapors.

2002 - No Leak Power Steering Sealer  
Part #2002

---

SECTION IV FIRE AND EXPLOSION HAZARD DATA

---

Flash Point: 392 F. (200 C.) TCC  
Flammable Limits: N/A  
Lower Explosive Limit (LEL): N/A  
Upper Explosive Limit (UEL): N/A  
Extinguishing Media  
Use carbon dioxide, dry chemical, foam and/or water fog as extinguishing media.  
Special Fire Fighting Procedures  
None  
Unusual Fire and Explosion Hazards  
Water may cause frothing.

---

SECTION V REACTIVITY DATA

---

Stable: Yes  
Hazardous Polymerization May Occur: No  
Conditions to Avoid  
Store below 150 F. Do not apply high heat or flame to container. Keep separate from strong oxidizing agents.  
Incompatibility (Material to Avoid)  
Strong oxidants.  
Hazardous Decomposition or Byproducts  
Carbon dioxide (Carbon monoxide under incomplete combustion)

---

SECTION VI HEALTH HAZARD DATA

---

Effects on Eyes  
Mild irritant.  
Effects on Skin  
Mild irritant.  
Effects Due to Ingestion  
Toxicity is relatively low, there is a risk of aspiration of product into the lungs. On ingestion of large quantities, slight GI discomfort, diarrhea, and headache may occur. Small doses may produce irritation and diarrhea.  
Effects Due to Inhalation  
Low risk of inhalation. Mists above TLV may cause chemical pneumonitis.  
First Aid Procedures for Eyes  
If the product contacts the eyes, immediately wash the eyes with large quantities of room temperature water for at least 15 minutes, occasionally lifting the lower and upper lids. Get medical attention immediately.  
First Aid Procedures for Skin  
If the product contacts the skin, promptly wash the contaminated skin with soap and water for at least 15 minutes. If this product penetrates the clothing, promptly remove the clothing and wash the skin with soap and water.  
First Aid Procedures for Ingestion  
Do not induce vomiting. Get immediate medical assistance.  
First Aid Procedures for Inhalation  
Move the exposed person to fresh air at once and call emergency medical care. If breathing has stopped, give artificial respiration. If breathing is difficult, give humidified oxygen.

**2002 - No Leak Power Steering Sealer  
Part #2002**

---

**SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE**

---

**Steps to Be Taken in Case Material is Released or Spilled**

SMALL SPILL: Remove sources of heat or ignition, provide adequate ventilation, contain leak absorbent, inert, non-combustible material. LARGE SPILL: Contain spill, transfer to secure containers. In the event of an uncontrolled material release, the user should determine if release is reportable under applicable laws and regulations.

**Waste Disposal Method**

Dispose of product in accordance with local, state, and federal regulations. Before attempting clean up, refer other sections of MSDS for hazard warning information.

**Precautions to Be Taken in Handling and Storing**

See other sections of MSDS

**Other Precautions**

Product is combustible, handle accordingly.

---

**SECTION VIII CONTROL MEASURES**

---

**Local Exhaust:** Provide local ventilation to maintain exposure levels below recommended exposure limits.

**Mechanical (General):** In confined spaces, mechanical ventilation may be required.

**Special Ventilation:** OSHA TWA 5mg/m<sup>3</sup> Oil Mist

**Other Ventilation:** N/A

**Protective Gloves:** Use oil impervious gloves as required.

**Eye Protection:** Use safety goggles or chemical splash goggles as required.

**Other Protective Clothing or Equipment**

If there is a possibility of exposure of an individual's body to the lubricating oil, wear body-covering work clothes to avoid prolonged or repeated exposure.

**Work/Hygienic Practices**

Use normal hygiene practices.

**Respiratory Protection (Specify Type)**

Normally none required. If high vapor or mist concentrations are expected, use appropriate NIOSH approved respirator for organic vapors and mists.

---

**SECTION IX ADDITIONAL INFORMATION**

---

**Additional Information**

SHIPPING INFORMATION (CFR 49 AND IMDG):

PROPER SHIPPING NAME: Lubricating Oil, N.O.I.

DOT HAZARD CLASS : None required

DOT UN NUMBER : None required

IMDG SHIPPING NAME : Petroleum Lubricating Oil, N.O.I.

Flashpoint >160 F.

SARA TITLE III:

Section 302: None

Section 304: None

Section 311: Hazard categories-Fire Hazard=Yes

2002 - No Leak Power Steering Sealer  
Part #2002

---

SECTION IX ADDITIONAL INFORMATION (cont.)

---

Additional Information (cont.)

Section 313: None

CERCLA:

Section 311(b)(4): Requires discharges of crude oil and petroleum products in any kind or form to waters must immediately be reported to the National Response Center at (800) 424-8802.

DISCLAIMER: Information presented herein is believed to be factual, as it has been derived from the works and opinions of persons believed to be qualified experts. However, nothing contained in this information is to be taken as warranty or representation for which the Gold Eagle Co. bears legal responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.

Prepared by: Mike Profetto

While the information and recommendations set forth herein are believed to be accurate as of the MSDS date, Corbus, a division of Compliance Management Systems, Inc., makes no warranties expressed or implied of fitness for a particular purpose with respect hereto and disclaims all liability from reliance thereon.